

ML5790eco/ML5791eco Specifications



24-pin dot matrix printer perfect for front desk printing

For fast, reliable, superior quality printing in retail and service industries and all types of invoice and order printing applications

The ML5790eco and wide carriage ML5791eco are ideal where fast printing, reliability, versatile paper handling and superior quality text is essential. Whether you are printing invoices, purchase orders, spreadsheets, picking lists, call log slips, tickets, receipts or multi-part documents, the ML5790eco/ML5791eco keeps your transactions smooth and your customers happy. The small footprint of the ML5790 is ideal for businesses where space is limited, for example, at the front desk of banks, travel agents, stations or surgeries.

Flexible, Eco-friendly and cost effective

The ML5790eco/5791eco have been developed with eco-friendly technology. With power consumption of just 1.5w in sleep mode, your running costs and energy consumption are kept to a minimum, as well as reducing your carbon footprint.

More paper paths give you flexibility. The three tractor feeding paths handle multi-part forms and continuous paper from either the front, rear or bottom. The two friction feeding paths handle cut-sheets, cards and envelopes from either the front or top.

A selection of pull and push tractors allow permanent stationary loading, for use on demand and handle multi-part and continuous forms more efficiently. The optional Roll Paper Stand

(ML5790eco only) is a cost effective option for applications with variable paper lengths.

OKI's commitment to our customers

The OKI brand is one of proven reliability and value. We provide printers that increase our customers' long-term business performance without impacting their budget.

With almost half a century of experience in the impact printer industry, with OKI you are guaranteed a best-in-class, low cost, reliable and easy to use printer. And, for total peace of mind just register your product and take advantage of our extended three-year warranty at no extra cost.

Key Benefits:

Faster transactions

- Flies through up to 7-part forms and reports at print speeds of up to 576 characters per second for speedier transactions

Superior print quality

- 24-pins deliver sharper, detailed text
- Scalable fonts for superior print quality
- Letter quality output for customer receipts

Tough and reliable

- Operates in the most challenging environments
- Mean Time Between Failure (MTBF) figure of 25,000 hours

Easy to install and use

- On-board Epson and IBM compatibility for trouble free plug and print
- Simple 'Clean hands' ribbon changing ensures no delay, mess or hassle when fitting a new ribbon

Save money

- Long life ribbon (8 million characters ML5790eco, 13 million characters ML5791eco)
- Low energy consumption in Sleep mode
- Low cost per page

Flexible paper handling

- Four paper paths can handle forms, cut-sheet and continuous sheets

Environmentally friendly

- Eco-friendly technology, sleep mode consumes just 1.5W
- Manufactured at a carbonzero rated facility

A4/A3 ✓

Range of media handling ✓

Print ✓

1-30 users ✓

Variants available:

ML5790eco
Narrow carriage
ML5791eco
Wide carriage



ML5790eco/ML5791eco - Dot Matrix Printers

| PRINTER | |
|-----------------|--|
| Number of pins | 24 |
| Columns | ML5790eco: 80(10cpi); 160 (maximum in compression mode) ML5791eco: 136(10cpi); 272 (maximum in compression mode) |
| Character pitch | 5/6/7.5/8.5/10/12/15/17.1/20 pitch and proportional |
| Print speed | High Speed Draft: 576cps (12cpi); High Speed Draft: 480cps (10cpi); Draft: 540cps (15cpi); Draft: 432cps (12cpi); Draft: 360cps (10/20cpi); Draft: 309cps (17.1cpi); Letter Quality: 240cps (20cpi); Letter Quality: 206cps (17.1cpi); Letter Quality: 180cps (15cpi); Letter Quality: 144cps (12cpi); Letter Quality: 120cps (10cpi) |

| INTERFACE AND SOFTWARE | |
|-----------------------------|---|
| Interfaces | IEEE 1824 parallel interface, USB 2.0 (full speed) |
| Optional interfaces | Ethernet 10/100, Serial RS232C |
| Emulations | Epson LQ ESC/P2, IBM PPR, IBM AGM |
| Typeface & font | HSD, Draft, Courier (scalable), Roman (scalable), Swiss (scalable), Swiss Bold, Orator, Gothic, Prestige, OCR-A, OCR-B |
| Typestyle | Emphasised, Enhanced, Double Width, Double Height, Italics, Outline, Shadow, Superscript, Subscript, Underline |
| Barcode fonts | UPC-A, UPC-E, EAN8, EAN13, Code39, Interleaved 2of5, Code128(A/B/C), CODABAR (NW-7), POSTNET, Industrial 2of5, Matrix 2of5 |
| Printer driver ¹ | Windows 2000 / XP (32-bit & 64-bit) / Vista (32-bit & 64-bit) / 7 (32-bit & 64-bit) / Server 2003 (32-bit & 64-bit) / Server 2008 (32-bit & 64-bit) / Server 2008 R2 (64-bit) |
| Utilities | Status monitor, Button setup utility, Menu setup utility, TOF setup utility |

| PAPER HANDLING | |
|---|---|
| Paper | Cut Sheet (single sheet), Continuous Paper (single-part, multi-part), Roll paper (ML5790eco only), Envelope, Card, Label (cut sheet and fan fold) |
| Continuous paper (width) | ML5790eco: 76.2 - 254.0mm; ML5791eco: 76.2 - 406.4mm |
| Continuous paper (length) | 76.2 - 558.8mm |
| First printable line (from top of page) | Continuous: 2.12mm; Cut sheet: 0.5mm |
| Copy capability | Up to 1 original + 4 copies (Pull tractor); Up to 1 original + 5 (Push tractor) |
| Multi-part paper thickness | Front/rear push feed: 0.36mm; Front/rear pull feed & front/rear push-pull feed: 0.44mm; Bottom pull feed: 0.48mm |
| Paper feeding | Manual insertion: Front or rear in, top out; Push Tractor: Front or rear in, top out; Pull tractor: Front or rear or bottom in, top out |
| Optional paper feeding | Single Bin Cut Sheet Feeder, Push Tractor (front/rear feeds), Pull Tractor (bottom feed), Roll Paper Stand (ML5790eco only) |

¹Check local OKI Printing Solutions website for latest driver releases and OS compatibility

Consumables Information: Only use genuine OKI Printing Solutions Original consumables to ensure the best quality and performance from your hardware. Non OKI Printing Solutions Original products may damage your printer's performance and invalidate your warranty.

| GENERAL FEATURES | |
|-----------------------|--|
| Input buffer | 128Kbytes |
| Power supply | Single phase 220 to 240VAC, +/- 10% |
| Power consumption | ISO/IEC 10561 Letter, Draft, Range1: 88W; Sleep mode:1.5W (with no optional attachments) |
| Noise level | Normal: 57dB(A); Quiet: 52dB(A); Silent mode: 49dB(A) |
| Dimensions (HxWxD) | ML5790eco: 191 x 438 x 375mm; ML5791eco: 191 x 592 x 375mm |
| Weight | ML5790eco: 7.5kg approx; ML5791eco: 10kg approx |
| Print Head life | 400 million characters |
| Reliability | MTBF: 25,000 hours |
| Product order numbers | ML5790eco: 44210108; ML5791eco: 44210208 |

| ACCESSORIES (ORDER NUMBERS) | |
|---------------------------------|--|
| Single Bin Cut Sheet Feeder | ML5790eco: 44497403; ML5791eco: 44497503 |
| Push Tractor (front/rear feeds) | ML5790eco: 44454903; ML5791eco: 44455003 |
| Pull Tractor (bottom feed) | ML5720eco: 44753903; ML5721eco: 44754003 |
| Roll Paper Stand | YA4053-10576016 (ML5790eco) |
| Serial RS232C | 44455103 |
| Ethernet 10/100 | 44455303 |

| CONSUMABLES (ORDER NUMBERS) | |
|--------------------------------|----------------------|
| Ribbon (8 million characters) | 44173407 (ML5790eco) |
| Ribbon (13 million characters) | 44173408 (ML5791eco) |

OKI DATA (SINGAPORE) PTE LTD.
438A Alexandra Road
#02-11/12
Alexandra Technopark
Singapore 119967
Tel: (65) 6221 3722
WWW.OKI.COM.SG

OKI DATA (SINGAPORE) PTE LTD.
Malaysia Rep Office
Suite 21.03, 21st Floor
Menara IGB, Mid Valley City
59200 Kuala Lumpur, Malaysia
Tel: (03) 2287 1177
: 1800 88 1177 (Toll Free)
Fax: (03) 2287 1166
WWW.OKI.COM.MY

OKI SYSTEMS (THAILAND) LTD.
1168/81-82 Lumpini Tower,
27th Floor Rama IV Road
Tungmahamek, Sathorn
Bangkok 10120
Tel: (662) 679 9235
Fax: (662) 679 9243/245
WWW.OKISYSSTHAI.COM

OKI SYSTEMS (HONG KONG) LTD.
Suite 1908, 19/F, Tower 3,
China Hong Kong City
33 Canton Road, TsimShaTsui,
Kowloon, Hong Kong
Tel: (852) 3543 9288
Fax: (852) 3549 6040
WWW.OKIPRINTINGSOLUTIONS.COM.HK

OKI DATA AUSTRALIA PTY LTD
146 O'Riordan Street,
Mascot NSW 2020
Toll Free: 1800 800 140
Tel: 02 9667 7240
WWW.OKIPRINTINGSOLUTIONS.COM.AU



Specification subject to change without notice. All trademarks acknowledged.

OKI
PRINTING SOLUTIONS