

## ML4410 DOT MATRIX PRINTER



### ❖❖❖ ML4410 ❖❖❖ DUAL 9-PIN DOT MATRIX PRINTER

#### THE DEFINITION OF DURABILITY AND PERFORMANCE

The ML4410 is the flagship model in Oki's Microline range. It has been designed to handle multi-part listings at extremely high speeds, with reliability and superior throughput. With low cost of ownership it is ideal.

#### MAIN FEATURES OF THE ML4410 PRINTER

- ❖❖❖ Super speed, 136 column dot matrix printer
- ❖❖❖ Dual 9-pin ultra reliable print head
- ❖❖❖ Up to 1066 characters per second print speed
- ❖❖❖ Multi-part paper-handling (original + 9 copies)
- ❖❖❖ Ideal for high volume tasks such as accounts, finance and IT - superb speed for listings and computer printouts
- ❖❖❖ Ideal for purchasing and distribution applications (up to 10 part paper)



# OKI

# ML4410 DOT MATRIX PRINTER

## PRODUCT SPECIFICATION

		ML4410
<b>General</b>	Number of pins	18 (2x9)
	No. of multi-part forms	Front feed: 10 (one original + 9 copies); Rear feed: 6 (one original + 5 copies)
<b>Speed &amp; throughput</b>	High speed draft (10cpi)	1066cps
	Utility (10cpi)	800cps
	Near letter quality (10cpi)	200cps
	Fastest print speed	1066cps
<b>Font &amp; print features</b>	Carriage width (10cpi)	136 columns
	Max. in compressed mode	272 columns
	Character pitch	10/12/15/17.1/20cpi & proportional
	Graphics resolution	Up to 240(H) x 216(V)
	Typeface & Font	NLQ-Courier (Scalable), NLQ-Gothic (Scalable), OCR-B, High Speed Draft, Utility + Barcodes
Typestyle	Emphasised, Enhanced, Double Width, Double Height, Italics, Underline, Superscript, Subscript, Overscore	
<b>Emulations &amp; interfaces</b>	Printer emulations	Epson FX, IBM ProPrinter, Oki MicroLine
	Standard interfaces	Centronics Parallel - IEEE 1284, Serial RS 232C
	Optional interfaces	Oki HSP Network interface card
	Control panel	2 x 16 backlit LCD, 13 button with configuration memories
	OS Compatibility	Novell Netware certified, Microsoft Plug & Play
<b>Paper-handling</b>	Continuous paper	76—419mm
	First printable line (from top of page)	Continuous: 8.9mm
	Standard	Autoload, Paper parking, Rear push tractors, Front (straight) push tractors, Auto bail arm, Auto gap, Software selectable paper paths
	Optional	Dedicated stand/cabinet with paper storage and output tray
<b>Physical</b>	Dimensions (HxWxD)	358 x 768 x 385mm
	Weight	42kg
	Memory (Total RAM)	512KB (max. 256KB addressable); Receive buffer: max. 56KB
	Flash ROM	8MB for code pages, emulations and macros
	Noise level (ISO 7779)	55dB(A) (quiet mode - Utility); 52dB(A) (quiet mode - NLQ)
<b>Power</b>	Power requirements	230V AC
	Frequency	50/60Hz ± 2%
<b>Reliability</b>	Print head life	400 million characters at 10cpi utility, 25% duty and 35% page density
	Ribbon life	15 million characters
<b>Supplies life</b>	MTBF	12,000 hours

# OKI

Only use genuine Oki Original consumables to ensure the best quality and performance from your hardware. Non Oki Original products may damage your printer's performance and invalidate your warranty. Specifications subject to change without notice. All trademarks acknowledged.

Okī, Network Solutions  
for a Global Society

OKI EUROPE, PART OF OKI ELECTRIC

OKI EUROPE LTD,  
CENTRAL HOUSE, BALFOUR ROAD,  
HOUNSLOW, MIDDLESEX, TW3 1HY,  
UNITED KINGDOM  
TEL: +44 (0)20 8219 2190  
FAX: +44 (0)20 8219 2199  
[WWW.OKIEUROPE.COM](http://WWW.OKIEUROPE.COM)



As an ENERGY STAR Partner, Oki Europe Ltd has determined that this product meets the ENERGY STAR guidelines for energy efficiency

©2003 Oki Europe Ltd.